

TYPE ZS 0006, ZS 0012,  
ZS 0018



## Basic Information

The lit-through “**Stop marker**” (the stop pole) is designed for marking the UMT stops.

It is used for informing the UMT (streetcars, busses, trolleybuses) passengers on actual transport lines, including timetables for the given UMT stop.

## Technical Description

With its technical equipment and design, the stop marker complies with today’s modern design of the UMT stops and the city vehicle fleet. The marker is available in several variants that differ from each other by the number of lines (the line number with the respective timetable). A steel pole with the diameter of 76 mm is the marker’s basic support element.

**Three boxes** made of drawn aluminium channel are fixed to the **pole**. The corners of the boxes are rounded so that they do not pose any danger with sharp edges. The front walls are covered with clear hardened glass or with clear polycarbonate.

The pole’s top is furnished with a box bearing a pictogram of the transportation vehicle type. The pictogram’s box is lit-through by a circular discharge lamp, and the bottom boxes with linear discharge lamps. Each luminous source has its own electronic starter. The boxes are accessible after tilting the door. All the boxes, including the support pole, are finished with a **powder coat**.

For the blind, there is a label with information in Braille fixed on the sidewall of the bottom box.

The stop markers differ from each other by the size of the middle and bottom boxes.

### Stop marker types:

- ZS 0006 – for accommodating up to 6 lines
- ZS 0012 – for accommodating up to 12 lines
- ZS 0018 – for accommodating up to 18 lines

### Basic Technical Data

Type:	ZS 0006, (ZS 0012, ZS 0018)
Supply:	230 V / 50 Hz
Input:	Max. 100 W
Luminous source:	Fluorescent lamp (5 units)
Protection:	IP43
Operation temperature:	-15°C up to +50°C
Dimensions (WxHxD):	Max. 520x3, 240x170 mm
Mass:	50 kg

### ZS 0006 Type



### Contact

**ELTODO EG, a.s.**  
Novodvorská 1010/14  
142 01 Praha 4, Czech Republic  
Phone: +420 261 346 828  
Fax: +420 261 346 803  
E-mail: [eltodo@eltodo.cz](mailto:eltodo@eltodo.cz)  
<http://www.eltodo.cz>